TECHNICAL SPECIFICATIONS

POWER ZOOM ADAPTER PZ-E2/ **POWER ZOOM ADAPTER PZ-E2B**

Drive mechanism Zoom operation

DC motor and gear reduction mechanism Wide (W) and Telephoto (T) buttons

(or assign customisable buttons on the camera with compatible cameras)

Remote operation (via Camera Connect / EOS Utility / Browser Remote / XC Protocol, with

compatible cameras)

(1) High-speed Mode (1.5 sec to 90 sec)*
(2) Normal Mode (3 sec to 90 sec)* Zoom speed

*Zoom speed selectable from the Zoom Speed Adjustment Dial Zoom mode switch

Servo zoom [SERVO] Manual zoom [MANU]

Attaches/detaches with coin-tightening screws (×3) Attachment method

USB-C interface External interfaces

(communication / external PD power)

20-pin interface (Power Zoom Adapter PZ-E2B only, for compatible lens zoom/focus demands and Canon's Zoom Servo Grip ZSG-C10)

Power supply from camera via lens Power

Power supply from digital terminal (USB-C terminal)*

*Cameras using lower power batteries may require external PD power to enable High-speed (zoom) Mode and enables extended shooting times

Yes, but does not fully prevent dust and moisture Dust/moisture resistance

intrusion

Approx. 105 x 81 x 60mm

(width x height x depth)

Weight

PZ-E2: Approx. 155 g (adapter only) PZ-E2B: Approx. 165 g (adapter only)

Accessories

Soft Case

USB Power Adapter PD-E1 (optional) Zoom Servo Grip ZSG-C10 (optional)¹ Zoom Demand ZSD-300D/380D (optional)¹ Focus Demand FPD-400D (optional)

Compatible lens RF 24-105mm F2.8L IS USM Z

FOOTNOTES

POWER ZOOM ADAPTER PZ-E2B only



Canon Inc. canon.com Canon Europe canon-europe.com English edition Canon Europa NV 2023